

# FUSE R

1180



ORDER

COST ESTIMATE

CUSTOM DESIGN

**Please fax the completed order form to: +49 5733 922 9311 Customer service: +49 5733 922 311**

Billing address / Customer ref. no.:

---

Delivery address:

---

Consignment / Comments:



## FUSE R 1.180

All prices subject to VAT at the prevailing rate! Valid from 01.01.2023 – 31.12.2023.  
 Our Terms and Conditions as stated at [www.meyra.de/AGB](http://www.meyra.de/AGB) shall apply.  
 Find out more about this product at [www.meyra.de](http://www.meyra.de).

### Specifications

Seat width	320 340 360 380 400 420 440 460 480 500	User weight	125
Width, ready to move, from	510 - 810	ready to move	from 8,5
seat depth	340 / 360 / 380 / 400 / 420 / 440 / 460 / 480 / 500	Permissible total weight	140
Seat height front / rear	450 to 530 / 390 to 500	Transport weight	from 5,6
Total height	Rear seat height + back height		
back height	telescopic up to 60 mm in 15 mm increments		
Length with footrest	760 - 860 (depending on frame length and wheel size)	Drive wheel	600 (24")
		Drive wheel	635 (25")
		Drive wheel	660 (26")
		Brake test according to STANDARD	7°

Dimensions in mm, weights in kg, wheels in inches, dimension tolerance  $\pm 10$  mm  
 Visit [www.meyra.de/measuring](http://www.meyra.de/measuring) for guidance on measuring.

#### Caution!

Please note when using public transport (e.g. trains): the dimensions of the wheelchair may exceed the transport company guidelines. Please enquire beforehand.  
 When using auxiliary drives, the permissible total weight must not be exceeded.

Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

## 00 Frame design (frame length)

	CODE	DESCRIPTION	FSH IN MM	OL IN MM
<input type="checkbox"/>	351	Frame short	450 - 490	760 - 840
<input type="checkbox"/>	352	Frame, standard	470 - 510	800 - 880
<input type="checkbox"/>	353	Frame long	480 - 530	840 - 920

Please bear in mind your seat depth and specify this accordingly in category 02!

## Frame design (frame angle and frame inset)

	CODE	DESCRIPTION	
<input type="checkbox"/>	346	Standard front frame	80°
<input type="checkbox"/>	347	Compact front frame	88°
<input type="checkbox"/>	4950	With frame inset, (20 mm per side)	
<input type="checkbox"/>	4959	Without frame inset	

## 01 Seat width (SW)

	CODE	DESCRIPTION
<input type="checkbox"/>	32	SW 320 mm
<input type="checkbox"/>	34	SW 340 mm
<input type="checkbox"/>	36	SW 360 mm
<input type="checkbox"/>	38	SW 380 mm
<input type="checkbox"/>	40	SW 400 mm
<input type="checkbox"/>	342	SW 420 mm
<input type="checkbox"/>	344	SW 440 mm
<input type="checkbox"/>	46	SW 460 mm
<input type="checkbox"/>	48	SW 480 mm
<input type="checkbox"/>	350	SW 500 mm

Please select by ticking the relevant boxes

**Standard version:** If no other selection is made, the standard version will be delivered.

## 02 Seat depth (SD) Tension-adjustable seat belt

CODE	DESCRIPTION
<input type="checkbox"/> 394	SD 340 mm
<input type="checkbox"/> 366	SD 360 mm
<input type="checkbox"/> 368	SD 380 mm
<input type="checkbox"/> 615	SD 400 mm
<input type="checkbox"/> 784	SD 420 mm
<input type="checkbox"/> 618	SD 440 mm
<input type="checkbox"/> 619	SD 460 mm
<input type="checkbox"/> 787	SD 480 mm
<input type="checkbox"/> 792	SD 500 mm      incl. utensil bag under the seat belt

## 03 Front seat height (FSH) in combination with drive wheel size (without seat cushion)

Horizontal columns = seat heights in mm      Vertical lines = Ø drive wheel size in inches

Please select your required seat height by selecting a possible combination of seat height and drive wheel size. The maximum permitted seat height difference between front and rear seat height is 100 mm! Recommendation: Solid rubber castor wheels for heavier user weight

FSH	450	460	470	480	490	500	510	520	530
24" drive wheel	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
25" drive wheel		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
26" drive wheel			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## 04 Castor wheel tyres

CODE	DESCRIPTION	RIM	TYRES
<input type="checkbox"/> 151	100 mm castor wheel (pair)	Plastic	Solid rubber
<input type="checkbox"/> 325	125 mm castor wheel (pair)	Plastic	Solid rubber

### Castor wheel tyres

CODE	DESCRIPTION
<input type="checkbox"/> 908	Black tyres, only in conj. with CODE 151, 325
<input type="checkbox"/> 909	Grey tyres, only in conj. with CODE 151, 325

Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

### Castor wheels

CODE	DESCRIPTION	RIM	TYRES	Ø X W
<input type="checkbox"/> 2480	Lightwheel (pair)	Plastic, black	Solid rubber , transparent/colour	100 x 23 mm
<input type="checkbox"/> 2481	Swivel castor (pair)	Aluminium, silver	Solid rubber, black	100 x 32 mm
<input type="checkbox"/> 2482	Swivel castor (pair)	Aluminium, silver	Solid rubber, black	125 x 32 mm
<input type="checkbox"/> 2483	Swivel castor	Aluminium, silver	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2484	Swivel castor	Aluminium, black	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2485	Swivel castor	Aluminium, white	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2486	Swivel castor	Aluminium, red	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2487	Swivel castor	Aluminium, blue	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2488	Swivel castor	Aluminium, orange	Solid rubber, black	100 x 37 mm
<input type="checkbox"/> 2489	Swivel castor	Aluminium, silver	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2490	Swivel castor	Aluminium, black	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2491	Swivel castor	Aluminium, white	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2492	Swivel castor	Aluminium, red	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2493	Swivel castor	Aluminium, blue	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2494	Swivel castor	Aluminium, orange	Solid rubber, black	125 x 37 mm
<input type="checkbox"/> 2495	Swivel castor	Carbon fibre, black	Solid rubber, black	100 x 30 mm
<input type="checkbox"/> 2496	Swivel castor	Carbon fibre, black	Solid rubber, black	125 x 30 mm

### 05 Rear seat height (RSH) in combination with drive wheel (without seat cushion)

Horizontal columns = seat heights in mm      Vertical lines = Ø drive wheel

Please select your required seat height by selecting a possible combination of seat height and wheel size.

The maximum permitted seat height difference between front and rear seat height is 100 mm! 25" and 26" see Xtrends drive wheels

	390	400	410	420	430	440	450	460	470	480	490	500
Ø 24 x 1"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
Ø 25 x 1"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Ø 26 x 1"			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### Horizontal drive wheel position (gravity setting)

Information: The standard fine adjustment enables the centre of gravity to be adjusted by a further +/- 10mm.

USER TYPE	PASSIVE					AVERAGE			
	1	2	3	4	5	6	7	8	9
Position									
Distance * in mm	<input type="checkbox"/> 65	<input type="checkbox"/> 75	<input type="checkbox"/> 85	<input type="checkbox"/> 95	<input type="checkbox"/> 105	<input type="checkbox"/> 115	<input type="checkbox"/> 125	<input type="checkbox"/> 135	<input type="checkbox"/> 145

\* Measurement: rear edge of back tube to centre of axle in mm

Additional gravity settings are possible in combination with wheelbase extension CODE 880

Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

## 06 Drive wheels

	CODE	DESCRIPTION	Ø
<input type="checkbox"/>	651	Standard wheel, silver	24"
<input type="checkbox"/>	<small>New</small> 2651	Standard wheel, black	24"
<input type="checkbox"/>	848	SILVERDESIGN with radial spokes and high flange hub	24"
<input type="checkbox"/>	695	Active wheel with radial spokes, high flange hub, hollow section rim (Jumbo rim) black Recommended for user weight over 100 kg or dynamic driving style!	24" 25" 26"
<input type="checkbox"/>	752	"Light" wheel incl. Schwalbe RightRun light tyres and black aluminium hand rim, only in conjunction with 0° wheel camber CODE 423. Recommended for user weight up to 90 kg!	24"
<input type="checkbox"/>	2461	Day-Lite aluminium drive wheel, rim, hub and spokes black. Black aluminium hand rims and black MBL Gazelle tyres	24"



### Drive wheels

	CODE	DESCRIPTION	Ø X W
<input type="checkbox"/>	2465	Six star incl. 8 bar high-pressure tyres and aluminium hand rim (pair)	24 x 1"
<input type="checkbox"/>	2466	Cross wheel incl. all-terrain tyres and stainless steel hand rims (pair)	24 x 1.75"
<input type="checkbox"/>	2468	Day-Lite aluminium drive wheel, black rim, hub and spokes, black aluminium hand rims and black MBL Speedlite tyres	25 x 1"
<input type="checkbox"/>	2469	Spinergy CLX carbon fibre drive wheel, spokes and hub black	24 x 1"
<input type="checkbox"/>	2470	Spinergy LX aluminium drive wheel, spokes, rim and hub black	24 x 1"
<input type="checkbox"/>	2471	Spinergy LX aluminium drive wheel, rim and hub black, spokes white	24 x 1"
<input type="checkbox"/>	2472	Spinergy LX aluminium drive wheel, rim and hub black, spokes orange	24 x 1"
<input type="checkbox"/>	2473	Blacklight aluminium drive wheel, incl. Schwalbe Marathon Plus tyres and aluminium hand rims, rim, hub and spokes black	24 x 1"

### Drive wheel options

	CODE	DESCRIPTION
<input type="checkbox"/>	880	Wheelbase extension, adjustment range from -15 mm to 55 mm

Specification of the position selection



Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

### Wheel camber

CODE	DESCRIPTION
<input type="checkbox"/> 423	0° wheel camber
<input type="checkbox"/> 447	3° wheel camber (adjustable track)
<input type="checkbox"/> 454	6° wheel camber (adjustable track)

### 07 Hand rims and hand rim options

CODE	DESCRIPTION	Ø
<input type="checkbox"/> 493	Brightly polished stainless steel	24" 25" 26"
<input type="checkbox"/> 494	Aluminium, not in conjunction with Active wheel CODE 695	24"
<input type="checkbox"/> 445	Titanium, with 6 brackets, only in conj. with Active wheel CODE 695 and Spinergy wheel	24" 25" 26"
<input type="checkbox"/> 849	Curve L, aluminium black powder coated, ergonomic hand rim profile, H 31 mm, only in conj. with Active wheel CODE 695, standard wheel CODE 651 and 2651 and Spinergy	24"
<input type="checkbox"/> 850	Curve L Tetra Grip, slip-resistant coating, aluminium, suitable for tetraplegics, ergonomic hand rim profile, H 31 mm, only in conj. with Active wheel CODE 695, standard wheel CODE 651 and 2651 and Spinergy	24"
<input type="checkbox"/> 853	GEKKO, black powder coated aluminium with replaceable rubber lip, ergonomic hand rim profile, H 31 mm, only in conj. with Active wheel CODE 695, standard wheel CODE 651 and 2651 and Spinergy	24"
<input type="checkbox"/> 168	Optigripp special hand rim for tetraplegics	24"
<input type="checkbox"/> 166	Silicone hand rim cover, smooth, black, not in conj. with aluminium hand rims CODE 494 and the Spinergy drive wheel	24"
<input type="checkbox"/> 692	Narrow hand rim clearance	24"
<input type="checkbox"/> 693	Wide hand rim clearance	24"

Total width hand rim clearance see enclosed information.

### 08 Tyres (not in combination with Xtrends wheels)

CODE	DESCRIPTION	Ø
<input type="checkbox"/> 496	Pneumatic tyres, grey, 8 bar	24 x 1"
<input type="checkbox"/> 395	Maxxis VN Master Alpha Protect tyres black, puncture-resistant, 10 bar	24 x 1"
<input type="checkbox"/> 897	Schwalbe Marathon Plus Evolution tyres black, puncture-resistant, 10 bar	24 x 1" 25 x 1" 26 x 1"
<input type="checkbox"/> 363	Schwalbe ONE plain tread tyres, black, puncture-resistant, 9 bar	24 x 1"

See category 06 Seat height in combination with drive wheel.

**Note:** Tyres consist of a rubber compound which may leave permanent marks or be hard to remove from some surfaces (e.g. plastic, wooden or parquet flooring, rugs and carpets).

We cannot accept liability for any abrasion damage to flooring.

Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

## 09 Back strap height (BH)

	CODE	BH	DESCRIPTION
<input type="checkbox"/>	620	250 mm	Back strap, adjustable via hook and loop fasteners, additionally configurable + 60 mm in 15 mm increments
<input type="checkbox"/>	626	300 mm	Back strap, adjustable via hook and loop fasteners, additionally configurable + 60 mm in 15 mm increments
<input type="checkbox"/>	631	350 mm	Back strap, adjustable via hook and loop fasteners, additionally configurable + 60 mm in 15 mm increments
<input type="checkbox"/>	632	400 mm	Back strap, adjustable via hook and loop fasteners, additionally configurable + 60 mm in 15 mm increments
<input type="checkbox"/>	633	450 mm	Back strap, adjustable via hook and loop fasteners, additionally configurable + 50 mm in 15 mm increments

## 10 Back strap types

	CODE	DESCRIPTION
<input type="checkbox"/>	235	Textile, black
<input type="checkbox"/>	292	Net fabric, breathable, black
<input type="checkbox"/>	2002	Back cover width +20 mm, only in conjunction with CODE 235 or 292
<input type="checkbox"/>	2003	Back cover width +40 mm, only in conjunction with CODE 235 or 292
<input type="checkbox"/>	593	Without back cover, recommended when using RIDE back systems

### RIDE JAVA Back

DESCRIPTION	CODE
Please specify the CODE from the RIDE order sheet*	<input style="width: 150px; height: 20px;" type="text"/>

\* Caution: only in conj. with push handle CODE 410 and 412

## 11 Back rest (standard 90° to seat) fold to seat as standard, angle-adjustable and lockable (backrest angle: 95° / 90° / 85° / 80° / 75°)

	CODE	DESCRIPTION
<input type="checkbox"/>	410	Push handle, long
<input type="checkbox"/>	413	Back with push handle, short
<input type="checkbox"/>	411	Back without push handle
<input type="checkbox"/>	502	Back with push handle, mounted on back tube, infinitely variable height adjustment up to 150 mm from RH 300 mm possible
<input type="checkbox"/>	141	Push handles, swing-away from back height 300 mm up
<input type="checkbox"/>	2032	ErgoSeat Pro chest pelottes, small, pair. Recommended with back heights of 300 - 400 mm



Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

## 12 Seat cushion

CODE	DESCRIPTION
<input type="checkbox"/> 560	Seat cushion 30 mm
<input type="checkbox"/> 561	Seat cushion 60 mm
<input type="checkbox"/> 562	Fleece strips on seat belt

### RIDE JAVA seat cushions

DESCRIPTION	CODE
Please specify the CODE from the RIDE order sheet	<input type="text"/>

### RIDE Forward seat cushions

DESCRIPTION	CODE
Please specify the CODE from the RIDE order sheet	<input type="text"/>

### Netti Contour seat cushion

CODE	DESCRIPTION	COVER	WIDTH	DEPTH
<input type="checkbox"/> 7361	Netti Contour	Breathable 3D cover	40	40
<input type="checkbox"/> 7362	Netti Contour	Breathable 3D cover	40	45
<input type="checkbox"/> 7363	Netti Contour	Breathable 3D cover	43	40
<input type="checkbox"/> 7364	Netti Contour	Breathable 3D cover	43	45
<input type="checkbox"/> 7365	Netti Contour	Breathable 3D cover	45	40
<input type="checkbox"/> 7366	Netti Contour	Breathable 3D cover	45	45
<input type="checkbox"/> 7367	Netti Contour	Breathable 3D cover	45	50
<input type="checkbox"/> 7368	Netti Contour	Breathable 3D cover	50	45
<input type="checkbox"/> 7369	Netti Contour	Breathable 3D cover	50	50

## 13 Brakes

CODE	DESCRIPTION
<input type="checkbox"/> 305	Pressure brake for user
<input type="checkbox"/> 2595	"Light" aluminium scissor brake, swing-away
<input type="checkbox"/> <small>New</small> 681	Brake lever extension, hinged, permanently mounted only in conj. with CODE 305 and CODE 652
<input type="checkbox"/> 652	Pressure brake, brake lever cranking close to side panel

Please select by ticking the relevant boxes

**Standard version:** If no other selection is made, the standard version will be delivered.

## 14 Side panels and armrests

Please observe the marked functional properties!

1 = fixed 2 = swivel up 3 = detachable 4 = lockable 5 = height-adjustable armrest 6 = with wheel covering

CODE	DESCRIPTION	1	2	3	4	5	6
<input type="checkbox"/> 101	Plastic side panel including mudguard 41 mm			●			●
<input type="checkbox"/> 783	Carbon fibre side panel including mudguard 35 mm			●			●
<input type="checkbox"/> 24	Side panel bracket with swing-away padded armrest						
<input type="checkbox"/> 748	Aluminium side panel in frame colour with cold-proof lining including height-adjustable armrest (screw-retained)	●					●

## 15 Legrests

CODE	DESCRIPTION	LOWER LEG LENGTH
<input type="checkbox"/> <small>New</small> 311	Tubular footrest, aluminium, height-adjustable, matt black	360 - 480
<input type="checkbox"/> 312	One-piece footrest, height, depth and angle-adjustable	360 - 480
<input type="checkbox"/> 359	Calf strap	

**Required lower leg length in mm (measured without seat cushion)**  
Factory default setting of lower leg length from 360 to 480 mm possible.

## 16 Frame design

CODE	DESCRIPTION	COLOUR
<input type="checkbox"/> 2300	Reflective sticker	white
<input type="checkbox"/> 2301	Reflective sticker	black
<input type="checkbox"/> 2302	Reflective sticker	Tricolour
<input type="checkbox"/> 2303	Reflective sticker	Rainbow

### STICKER DESIGNS

<input type="checkbox"/> 2304	MEYRA design
<input type="checkbox"/> 2305	STRIPE design

**Caution:** When selecting a design, a colour must be selected (CODE 2300, 2301, 2302 or 2303)

Please select by ticking the relevant boxes

Standard version: If no other selection is made, the standard version will be delivered.

## 17 Frame colours

CODE	DESCRIPTION	CODE	DESCRIPTION
<input type="checkbox"/> 130	Titanium grey	<input type="checkbox"/> 4043	Brown metallic matt
<input type="checkbox"/> 183	Silver metallic	<input type="checkbox"/> 4044	Red metallic matt
<input type="checkbox"/> 186	Magic blue	<input type="checkbox"/> 4045	Signal white matt
<input type="checkbox"/> 216	Jet black	<input type="checkbox"/> 4046	Green metallic matt
<input type="checkbox"/> 206	Matt black	<input type="checkbox"/> 4047	Purple metallic matt
<input type="checkbox"/> 224	Blue metallic	<input type="checkbox"/> 4048	Copper metallic
<input type="checkbox"/> 227	Red metallic	<input type="checkbox"/> 4913	Cross orange
<input type="checkbox"/> 4023	Signal white	<input type="checkbox"/> 4922	Green metallic
<input type="checkbox"/> 4040	Downtown grey	<input type="checkbox"/> 4049	Olive green matt
<input type="checkbox"/> 4041	Magic blue matt	<input type="checkbox"/> 4050	Sky blue
<input type="checkbox"/> 4042	Blue metallic matt	<input type="checkbox"/> 4051	Chalk

Other frame colours possible on request at a surcharge!

## 18 Wheelchair options Hand protectors and spoke guards

CODE	DESCRIPTION
<input type="checkbox"/> 489	Transparent not in conj. with Spinerigy wheel

### Support castor wheels

<input type="checkbox"/> 728	Support castor wheels, 1 pair, swing-away (recommended), not in conj. with stepper tube CODE 309
<input type="checkbox"/> 729	One support castor wheel, swing-away, <b>left</b> -mounted
<input type="checkbox"/> 730	One support castor wheel, swing-away, <b>right</b> -mounted
<input type="checkbox"/> 309	Stepper tube (one pair)
<input type="checkbox"/> 4930	One stepper tube, left-mounted, not in conjunction with support castor wheels CODE 728/729
<input type="checkbox"/> 4931	One stepper tube, right-mounted, not in conjunction with support castor wheels CODE 728/730

### Other options

<input type="checkbox"/> 833	Retainer strap with buckle
<input type="checkbox"/> 819	Passive lighting
<input type="checkbox"/> 205542100	Hand compressor
<input type="checkbox"/> 951	Accessory net
<input type="checkbox"/> 970	Walking aid holder in conjunction with stepper tube

Date:

Signature:

As at: 2023-06-08

### USER DETAILS


First name*:	<input type="text"/>
Last name*:	<input type="text"/>
House no./street:	<input type="text"/>
Postcode:	<input type="text"/>
Town/City*:	<input type="text"/>
Country:	<input type="text"/>
Date of birth*:	<input type="text"/>
Diagnosis -1-:	<input type="text"/>
Diagnosis -2-:	<input type="text"/>
Tel. (landline):	<input type="text"/>
Tel. (mobile):	<input type="text"/>
E-mail:	<input type="text"/>
Order no.:	<input type="text"/>

Please note that fields marked \* are mandatory!

### BODY MEASUREMENTS (IN MM):

Please refer to the sketches in the enclosed information!

1) Seat depth*:	<input type="text"/>
2) Seat width*:	<input type="text"/>
3) Chest width:	<input type="text"/>
4) Chest depth:	<input type="text"/>
5) Elbow height:	<input type="text"/>
6) Arm pit height:	<input type="text"/>
7) Back height:	<input type="text"/>
8) Head height:	<input type="text"/>
9) Forearm length:	<input type="text"/>
10) Lower leg length*:	<input type="text"/>
Height*:	<input type="text"/>
Weight (kg)*:	<input type="text"/>



All seat dimensions are always measured without seat cushion!

I hereby confirm that all details are complete and correct.  
I consent to the information/data I provide and the photos/videos taken of me being passed on to MEYRA GmbH (Meyra-Ring 2, 32689 Kalletal, Germany) and specialist retailers for the purposes of implementing the contract/manufacturing the product.

.....  
Date/signature

It is hereby confirmed that all details are complete and correct.

.....  
Date/signature of the specialist retailer

# Equipment and coding




03

Article 1072385




03

Article 1072386




03

Article 1088444




06

CODE 848




06

CODE 651




06

CODE 695




06

CODE 752




06

Article 1068707



06

Article 1073640



06

Article 1068713



06

CODE 880




07

CODE 849



07

CODE 850



07

CODE 853



09

CODE 2595



10

CODE 2310




11

CODE 410



12

CODE 100



11

CODE 4312




11

CODE 141



13

CODE 305



13

CODE 652




14

CODE 312



12

CODE 748



17

CODE 729

## Equipment and coding

---




Article 1089204



Article 1089205



Article 1089206



Article 1089207



Article 1089208



Article 1089209



Article 1089210



Article 1089211